



The **Monstrum Tactical S3940-M-RG** is a full-featured scope suitable for hunting, target shooting, or tactical use. The scope comes equipped with:

- Adjustable 3-9 times magnification, for targeting out to 300 yards and beyond
- Adjustable reticle illumination with 5 brightness levels in both red and green, allowing for better reticle visibility at night or in low light environments
- ¼ MOA/click windage and elevation adjustments
   A Mil-Dot reticle with markings allowing for range and bullet drop estimation
- Aircraft grade 6061 aluminum construction, for lightweight and durable performance
- A sealed, nitrogen charged scope tube for resistance to fog and water

# **Monstrum Tactical 3-9x40 Scope**

S3940-M-RG

### MONSTRUMTACTICAL.COM



### Mounting the Scope:

- 1. Determine the proper eye relief for positioning the scope.
  Using the scope's adjustable magnification ring, set the scope to maximum magnification and look through the scope. The optimum eye relief is the farthest distance away from the scope from which you can still see the entire circular field of view. For the S3940-R-RG, the eye relief should be approximately 2 inches.
- 2. Set your scope mount and position your scope. Hold your rifle in a comfortable shooting position with your cheek welded to the stock. The scope should be mounted at a comfortable eye relief in relation to this position. Set your scope rings and position the scope accordingly.
- 3. Secure the scope. Tighten the mounting bolts securely. If necessary, apply a drop of loc-tite® to the threads of the screws to secure them.

### **Focusing the Scope**

The first step in focusing your scope, is adjusting the focus ring at the near end of the eyepiece. Please note that adjusting the focus ring does not bring the target image into focus. Adjusting the focus ring only focuses the eye on the reticle.

#### To adjust the focus ring:

- 1. With the scope pointed toward a blank wall or toward the sky, look through the scope.
- 2. Adjust the focus ring until the reticle is in sharp focus.

3

2


#### Sighting in your scope

Tip:


Before firing any rounds, we recommend bore sighting your rifle. Bore sighting refers to the process of aligning the bore of your rifle with your target, commonly done with a laser bore sighter, and then sighting in your optic accordingly. Bore sighting ahead of time will save you a significant amount of time and ammo, however, bore sighting alone is not enough to properly sight in your rifle. Once bore sighted, you are ready to sight in your scope.

#### To sight in your scope:

- 1. Position your target 100 yards away (or at whatever distance you wish to sight your scope at).
- 2. Position your rifle on a steady shooting platform such as a gun rest or bipod pointed at the target.
- 3. For variable magnification scopes, set your scope to the maximum magnification.
- 4. Fire one round at the center of the target, taking care not to change the position of the rifle.
- 5. Using a spotting scope or binoculars, identify the bullet hole on the target.
- 6. Using the windage and elevation adjustment dials on your scope, adjust the position of the crosshairs to align with the bullet hole. The elevation dial is located on top of the scope, while the windage dial is located on the right of the scope. Each click of the adjustment dial will move the position of the crosshairs by ¼ MOA or roughly ¼ inch at 100 yards.
- 7. Once the crosshairs are aligned with the bullet hole, aim again at the center of the target and repeat the process until you are consistently hitting the center of the target.
- 8. Once the scope has been zeroed, tighten the turret locks at the base of the windage and elevation dials to prevent the dials from moving.



5



## One Mil's Size at Various Distances

(in Yards)

100	200	300	400	500
3.6"	7.2"	10.8"	14.4"	18.0"
600	700	800	900	1000
21 6"	25 2"	28 8"	32 4"	36 N"

## **Warranty Support**

Monstrum Tactical ensures strict standards of quality control and provides a one year warranty with all of our rifle scope products. Please note, that to qualify for warranty support, scopes must be purchased new and include proof of purchase. For warranty support, please contact Monstrum Tactical at support@monstrumtactical.com.

7